



# prompt

The pursuit of purity

Our ideas and innovations are a part of the pursuit of maintaining the sanctity of milk so that the world's most ancient health drink can be appreciated as it truly is - untouched and unadulterated.



## Optimise your dairy business with related products

### AMCS

AMCS (Automatic Milk Collection System) is a comprehensive solution which digitizes and tracks the real-time information of milk collection process being followed at the collection centers. The cloud connectivity makes it possible to access the data from any location and BI Analytics Reports enable informed business decision making.




### DPMCU

Data Processing Milk Collection Unit (DPMCU) is an integrated milk collection software that accepts data from electronic Weighing Scale and Milk Analyzer. DPU (with cloud connectivity) then processes the data and prints milk slips through in-built printer for farmers.



### MilkoScreen

Milkoscreen accurately measures fat, SNF and protein based on proven FT-Infrared Technology. It also detects various adulterants such as added water, urea, sucrose, maltodextrin and ammonium sulphate present in the milk.



Prompt Equipments Pvt. Ltd.

3-B, Vardan Exclusive, Nr. Stadium Petrol Pump, Navarangpura,  
Ahmedabad - 380014, Gujarat, India

+91 7926565981/2/3 | info@promptdairytech.com | www.promptdairytech.com

follow us on

# prompt

The pursuit of purity

## INDIZ ULTRASONIC MILK ANALYZER

# How do we keep it pure?

Prompt provides innovative solutions for an efficient dairy procurement supply chain. From farm management and milk collection to quality analysis and preservation, we have different equipment and software to ensure that the purity of milk is retained at every step. Our unique offering, intelligent Milk

Analyzer, measures and records milk Fat, SNF, added water, milk density and has inbuilt features like power-on-self-test, App assisted online central calibration and ensures accuracy of readings. The system ensures transparency and optimum earnings to farmer and dairy.

## Our product in this pursuit – Indiz Ultrasonic Milk Analyzer

A PATENTED PRODUCT (PATENT NUMBER - 266880)

### INDIA'S FIRST SMART AND INTELLIGENT INDIGENOUS MILK TESTING EQUIPMENT

Our Milk Analyser provides accurate milk parameters reading and links it with the pay-out to farmer in real-time. In addition, all the data are stored online on cloud and can be accessed through Bluetooth enabled Mobile Application. This increases transparency and profitability arising out of improvement in the quality of milk collected.



Measures milk Fat, SNF, added water, and milk density



Being a 100% indigenous product, we offer service support across India



Preventive maintenance through Bluetooth-enabled Mobile application



Analyser available in Stainless Steel/ABS Body



Measuring time 30/40 seconds depending upon the model



Online central calibration



### INDIZ ULTRASONIC STIRRER

- Stirring removes air from fresh milk samples by vibrations created in the milk before testing
- Available in Powder Coated/ Stainless Steel housing
- Vibrator – SS Ball type/ Aluminium Ball Type

### VARIOUS PRODUCT VERSIONS AVAILABLE

|                                |   |
|--------------------------------|---|
| Indiz Ultrasonic Milk Analyser | Basic model with Measuring Time of 30/40 seconds  |
| Indiz PSM40                    | New design, Measuring Time – 40 seconds, Data Storage on SD card which can be exported through USB  |
| Indiz PSiM40                   | Measuring Time – 40 seconds, Online Central Calibration, Data Storage on Cloud, Preventive health check-up, Bluetooth enabled Mobile application* |

### SPECIFICATIONS

|                          |  |
|--------------------------|--|
| Measuring Parameters     | <ul style="list-style-type: none"> <li>• FAT from 1.5% to 12% with accuracy +/- 0.1%</li> <li>• SNF from 6% to 12% with accuracy +/- 0.2%</li> <li>• Added water to milk from 0% to 60% with accuracy +/-5%</li> <li>• Density: 1.0220 g/cm<sup>3</sup>-1.0360g/m<sup>3</sup> with accuracy +/- 0.0005 g/cm<sup>3</sup>.</li> <li>• Measuring time: 30/40 seconds/ sample</li> <li>• Resolution: ± 0.01% for FAT, ± 0.01% for SNF, ± 1% for added water +/- 0.0001 g/cm<sup>3</sup> for density.</li> <li>• Repeatability: +/- 0.03% for Fat, +/- 0.05% for SNF, +/- 0.75% for added water ± 0.0002 g/cm<sup>3</sup> for density.</li> </ul> |
| Display                  | 2 Line, 16 Character, Big LCD Display, 10mm Character Height   |
| Operating Facilities     | Cleaning, Single Curve Calibration, Error List, Suitable for Cow/ Buffalo/Mixed Milk   |
| Operating Voltage        | <ul style="list-style-type: none"> <li>• 220Volts + 15-20%, AC, 50 Hz</li> <li>• 12V DC +/- 8%</li> </ul>  |
| Interface                | RS 232   |
| Environmental Conditions | <ul style="list-style-type: none"> <li>• Ambient Air Temperature- 15°C TO 50°C</li> <li>• Relative Humidity- 30% to 80%</li> <li>• Milk Temperature- 5°C to 35°C</li> </ul>  |
| Power Consumption        | Average 30 watts, peak 90 watts  |
| Loose Accessories        | <ul style="list-style-type: none"> <li>• RS 232 serial cable- 1 no.</li> <li>• AC power cable with plug top- 1 no.</li> <li>• Battery power cable- 1 no.</li> <li>• 200 ml bottle of monthly cleaning solution for emergency- 1 no.</li> <li>• 200 ml bottle of daily cleaning solution- 1 no.</li> <li>• Measuring mug- 2 nos.</li> <li>• Operating manual (English)-1 no.</li> <li>• To remove air from fresh milk before testing table top, Ultrasonic Stirrer (Optional).</li> </ul>   |

### FEATURES

- Robust and easy to operate
- Fast and accurate result
- Low operating and maintenance cost
- Durable in all weather conditions
- Better repeatability and accuracy
- One touch analysis
- Equipment operates only when critical self-tests are passed leading to reduced downtime cost
- Detailed Equipment Parameter Analytics available through online data to provide predictive maintenance

### WHAT ARE ITS BENEFITS?

#### Transparency & fair payments to farmers

Due to online central calibration, farmers can be assured that the machine displays accurate milk parameters and is free from any adjustments due to manual intervention. No differences in FAT/ SNF reading at the dairy and Milk Collection Centre leads to optimal pay-out to the farmer, increases transparency and ensures the desired quality of milk.

#### Real time information on Cloud

All the historical data logs such as FAT, SNF, self-cleaning data, calibration data, etc. are maintained online on the cloud which can be accessed real-time. Various analytics can also be done using the data which provides actionable insights and helps in making informed business decisions.

#### Preventive Health Check-up

Milk Analyser would start operations only after it passes through critical self-tests. This ensures regular cleaning of machines, reduced downtime cost, and accurate operations of the machine.